



Substrate

Primer

Leveling  
mass (optional)

Self-leveling  
layer + EPDM

## MARINE FLOORING

# DECO DECK SOFT

COMFORT AND  
AESTHETICS

- IMO-CERTIFIED
- SEAMLESS
- MAINTENANCE-FRIENDLY
- HIGH LEVEL OF COMFORT
- UV- AND WEATHER-RESISTANT

The Herculan Marine Deco Deck Soft is a very comfortable floor finish with a highly aesthetical appearance. A combination of soft EPDM infill with a very strong, but relatively soft self-leveling layer. Completed with a very fine sanding process, it gives a unique floor finish of your choice.



# SYSTEM PROPERTIES

## GENERAL SYSTEM PROPERTIES



0575

Shore hardness	~ D 50
Elongation at break [DIN 53455]	~ 90%
Tensile strength [DIN 53455]	~ 4,0 MPa
Angle tear [DIN 53515]	~ 5,2 N/mm
Wear resistance [Taber CS17/1kg/1000 cycles]	~ 50,0 mg
Caloric value	20,2543 MJ/kg
Slip resistance	adjustable
Layer thickness	~ 4 mm
Available colors	RAL/NCS/Sikkens
Density self-leveling resin	~ 1,5 kg/m <sup>3</sup>
Optional:	
Leveling mass + density	SL Screed 500 ~ 0,9 - 1,2 kg/m <sup>3</sup> (adjustable) RC Screed IMO F ~ 1,5 kg/m <sup>3</sup>
Protection layer	Optional

**HERCULAN**  
HIGH PERFORMANCE FLOORING