

# EC-TYPE EXAMINATION CERTIFICATE (MODULE B)

Application of: Directive 2014/90/EU of 23 July 2014 on marine equipment (MED), issued as "Forskrift om Skipsutstyr" by the Norwegian Maritime Authority. This Certificate is issued by DNV GL AS under the authority of the Government of Norway.

**This is to certify:**

**That the Surface materials and floor coverings with low flame-spread characteristics: floor coverings**

with type designation(s)  
**Herculan PU 350 IMO F**

Issued to  
**Herculan B.V.**  
**Meerkerk, Utrecht, Netherlands**


is found to comply with the requirements in the following Regulations/Standards:  
Regulation **(EU) 2019/1397,**  
**item No. MED/3.18c. SOLAS 74, Reg. II-2/3, II-2/5, II-2/6 & X/3, IMO MSC/Circ. 1120, 2000 HSC Code 7 and IMO 2010 FTP Code**

Further details of the equipment and conditions for certification are given overleaf.

This Certificate is valid until **2024-12-09.**

Issued at **Høvik** on **2019-12-10**

DNV GL local station:  
**Netherlands CMC**



for **DNV GL AS**

Approval Engineer:  
**Nanna Martine Jacobsen**

Notified Body  
No.: **0575**

**Roald Vårheim**  
**Head of Notified Body**

A U.S. Coast Guard approval number will be assigned to the equipment when the production module has been completed and will appear on the production module certificate (module D, E or F), as allowed by the "Agreement between the United States of America and the EEA EFTA states on the mutual recognition of Certificates of Conformity for Marine Equipment" signed 17 October 2005, and amended by Decision No 1/2019 dated February 22nd, 2019.

The mark of conformity may only be affixed to the above type approved equipment and a Manufacturer's Declaration of Conformity issued when the production-surveillance module (D, E or F) of Annex B of the MED is fully complied with and controlled by a written inspection agreement with a Notified Body. The product liability rests with the manufacturer or his representative in accordance with Directive 2014/90/EU.

This certificate is valid for equipment, which is conform to the approved type. The manufacturer shall inform DNV GL AS of any changes to the approved equipment. This certificate remains valid unless suspended, withdrawn, recalled or cancelled.

Should the specified regulations or standards be amended during the validity of this certificate, the product is to be re-approved before being placed on board a vessel to which the amended regulations or standards apply.



## Product description

"Herculan PU 350 IMO F"

Is a two layered floor covering composed of:

1. one layer of 150 µm (dry film thickness) primer "Sigmaprime 200", a two-component multi-purpose, polyamide cured epoxy coating with density 1400 kg/m<sup>3</sup>, and
2. one layer of 100 µm (dry film thickness) topcoat "Herculan PU 350", a two-component polyurethane coating with density 1150 kg/m<sup>3</sup>.

Max. thickness: 150 µm (dry film thickness).

## Application/Limitation

Approved for use as low flame spread surface material, not generating excessive quantities of smoke nor toxic products in fire.

Approved for use as floor covering on a metallic substrate with thickness of at least 4.5 mm.

### Sigmaprime 200:

Approved colour: Grey, yellow/green, redbrown

Maximum organic content: 26%

### Herculan PU 350:

Approved colour: Blue and brighter colour

Maximum organic content: 45%

Several layers of floor coverings are acceptable provided that each layer is approved according to the Marine Equipment Directive and bear the mark of Conformity.

Each product is to be supplied with its manual for application and maintenance.

## Type Examination documentation

Test Report No. 16110B dated 24 September 2013 from Warrington Fire Gent, Gent, Belgium.

## Tests carried out

Tested according to IMO 2010 FTP Code part 5 and Annex 2 item 2.2 and 2.3.

## Marking of product

The product or packaging is to be marked with name and address of manufacturer, type designation, fire technical rating, the MED Mark of Conformity and USCG Approval Number if applicable (see first page).